



# STP55NE06 STP55NE06FP

N-CHANNEL 60V - 0.019  $\Omega$  - 55A TO-220/TO-220FP  
"SINGLE FEATURE SIZE™" POWER MOSFET

**Table 1. General Features**

Type	V <sub>DSS</sub>	R <sub>DS(on)</sub>	I <sub>D</sub>
STP55NE06	60 V	< 0.022 $\Omega$	55 A
STP55NE06FP	60 V	< 0.022 $\Omega$	30 A

### FEATURES SUMMARY

- TYPICAL R<sub>DS(on)</sub> = 0.019  $\Omega$
- EXCEPTIONAL dv/dt CAPABILITY
- 100% AVALANCHE TESTED
- LOW GATE CHARGE 100°C
- HIGH dv/dt CAPABILITY
- APPLICATION ORIENTED CHARACTERIZATION


### DESCRIPTION

This Mosfet is the latest development of STMicroelectronics unique "Single Feature Size" strip-based process. The resulting transistor shows extremely high packing density for low onresistance, rugged avalanche characteristics and less critical alignment steps therefore a remarkable manufacturing reproducibility.


### APPLICATIONS

- DC MOTOR CONTROL
- DC-DC & DC-AC CONVERTERS
- SYNCHRONOUS RECTIFICATION

**Figure 1. Package**



**Figure 2. Internal Schematic Diagram**



**Table 2. Order Codes**

Part Number	Marking	Package	Packaging
STP55NE06	P55NE06	TO-220	TUBE
STP55NE06FP	P55NE06FP	TO-220FP	TUBE

## STP55NE06/FP

**Table 3. Absolute Maximum Ratings**

Symbol	Parameter	Value		Unit
		STP55NE06	STP55NE06FP	
V <sub>DS</sub>	Drain-source Voltage (V <sub>GS</sub> = 0)	60		V
V <sub>DGR</sub>	Drain- gate Voltage (R <sub>GS</sub> = 20 kΩ)	60		V
V <sub>GS</sub>	Gate-source Voltage	± 20		V
I <sub>D</sub>	Drain Current (cont.) at T <sub>C</sub> = 25 °C	55	30	A
I <sub>D</sub>	Drain Current (cont.) at T <sub>C</sub> = 100 °C	39	21	A
I <sub>DM</sub> (1)	Drain Current (pulsed)	220	220	A
P <sub>tot</sub>	Total Dissipation at T <sub>C</sub> = 25 °C	130	35	W
	Derating Factor	0.96	0.27	W/°C
dv/dt (2)	Peak Diode Recovery voltage slope	4.5	4.5	V/ns
V <sub>ISO</sub>	Insulation Withstand Voltage (DC)	–	2000	V
T <sub>stg</sub>	Storage Temperature	-65 to 175		°C
T <sub>j</sub>	Max. Operating Junction Temperature	175		°C

Note: 1. Pulse width limited by safe operating area  
 2. I<sub>SD</sub> ≤ 55A, di/dt ≤ 300 A/μs, V<sub>DD</sub> ≤ V<sub>(BR)DSS</sub>, T<sub>j</sub> ≤ T<sub>JMAX</sub>

**Table 4. Thermal Data**

Symbol	Parameter	Value		Unit
		TO-220	TO220-FP	
R <sub>thj-case</sub>	Thermal Resistance Junction-case Max	1.15	4.28	°C/W
R <sub>thj-amb</sub>	Thermal Resistance Junction-ambient Max	62.5		°C/W
T <sub>l</sub>	Maximum Lead Temperature For Soldering Purpose	300		°C

**Table 5. Avalanche Characteristics**

Symbol	Parameter	Max Value	Unit
I <sub>AR</sub>	Avalanche Current, Repetitive or Not-Repetitive (pulse width limited by T <sub>j</sub> max, δ < 1%)	55	A
E <sub>AS</sub>	Single Pulse Avalanche Energy (starting T <sub>j</sub> = 25 °C; I <sub>D</sub> = I <sub>AR</sub> ; V <sub>DD</sub> = 25 V)	200	mJ

**ELECTRICAL CHARACTERISTICS** ( $T_{\text{case}} = 25^{\circ}\text{C}$  unless otherwise specified)**Table 6. Off**

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
$V_{(\text{BR})\text{DSS}}$	Drain-source Breakdown Voltage	$I_{\text{D}} = 250 \mu\text{A}; V_{\text{GS}} = 0$	60			V
$I_{\text{DSS}}$	Zero Gate Voltage	$V_{\text{DS}} = \text{Max Rating}$			1	$\mu\text{A}$
	Drain Current ( $V_{\text{GS}} = 0$ )	$V_{\text{DS}} = \text{Max Rating } T_{\text{c}} = 125^{\circ}\text{C}$			10	$\mu\text{A}$
$I_{\text{GSS}}$	Gate-body Leakage Current ( $V_{\text{DS}} = 0$ )	$V_{\text{GS}} = \pm 20 \text{ V}$			$\pm 100$	nA

**Table 7. On (1)**

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
$V_{\text{GS}(\text{th})}$	Gate Threshold Voltage	$V_{\text{DS}} = V_{\text{GS}}; I_{\text{D}} = 250 \mu\text{A}$	2	3	4	V
$R_{\text{DS}(\text{on})}$	Static Drain-source On Resistance	$V_{\text{GS}} = 10\text{V}; I_{\text{D}} = 27.5 \text{ A}$		0.019	0.022	$\Omega$

Note: 1. Pulsed: Pulse duration = 300  $\mu\text{s}$ , duty cycle 1.5 %

**Table 8. Dynamic**

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
$g_{\text{fs}}$ (1)	Forward Transconductance	$V_{\text{DS}} > I_{\text{D}(\text{on})} \times R_{\text{DS}(\text{on})\text{max}}; I_{\text{D}} = 27.5 \text{ A}$	25	35		S
$C_{\text{iss}}$	Input Capacitance	$V_{\text{DS}} = 25 \text{ V}; f = 1 \text{ MHz}; V_{\text{GS}} = 0$		3050	4000	pF
$C_{\text{oss}}$	Output Capacitance			380	500	pF
$C_{\text{rss}}$	Reverse Transfer Capacitance			100	130	pF

Note: 1. Pulsed: Pulse duration = 300  $\mu\text{s}$ , duty cycle 1.5 %

**Table 9. Switching On**

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
$t_{\text{d}(\text{on})}$	Turn-on Time	$V_{\text{DD}} = 30 \text{ V}; I_{\text{D}} = 27.5 \text{ A}; R_{\text{G}} = 4.7 \Omega$		30	40	ns
$t_{\text{r}}$	Rise Time	$V_{\text{GS}} = 10 \text{ V}$ (see test circuit, Figure 18)		120	160	ns
$Q_{\text{g}}$	Total Gate Charge	$V_{\text{DD}} = 48 \text{ V}; I_{\text{D}} = 55 \text{ A}; V_{\text{GS}} = 10 \text{ V}$		80	105	nC
$Q_{\text{gs}}$	Gate-Source Charge			13		nC
$Q_{\text{gd}}$	Gate-Drain Charge			25		nC

**Table 10. Switching Off**

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
$t_{\text{r}(\text{Voff})}$	Off-voltage Rise Time	$V_{\text{DD}} = 48 \text{ V}; I_{\text{D}} = 55 \text{ A}; R_{\text{G}} = 4.7 \Omega$		20	30	ns
$t_{\text{f}}$	Fall Time	$V_{\text{GS}} = 10 \text{ V}$ (see test circuit, Figure 20)		50	70	ns
$t_{\text{c}}$	Cross-over Time			75	100	ns

Table 11. Source Drain Diode

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
$I_{SD}$	Source-drain Current				55	A
$I_{SDM}^{(1)}$	Source-drain Current (pulsed)				220	A
$V_{SD}^{(2)}$	Forward On Voltage	$I_{SD} = 60\text{ A}; V_{GS} = 0$			1.5	V
$t_{rr}$	Reverse Recovery Time	$I_{SD} = 55\text{ A}; di/dt = 100\text{ A}/\mu\text{s}$		110		ns
$Q_{rr}$	Reverse RecoveryCharge	$V_{DD} = 30\text{ V}; T_j = 150\text{ }^\circ\text{C}$ (see test circuit, Figure 20)		430		$\mu\text{C}$
$I_{RRAM}$	Reverse RecoveryCharge			7.5		A

Note: 1. Pulse width limited by safe operating area  
 2. Pulsed: Pulse duration = 300  $\mu\text{s}$ , duty cycle 1.5 %

Figure 3. Safe Operating Area for TO-220




Figure 4. Safe Operating Area for TO-220FP




Figure 5. Thermal Impedance for TO-220




Figure 6. Thermal Impedance for TO-220FP




Figure 7. Output Characteristics




Figure 8. Transfer Characteristics




Figure 9. Transconductance




Figure 10. Static Drain-source On Resistance




Figure 11. Gate Charge vs Gate-source Voltage







Figure 12. Capacitance Variations




**Figure 13. Normalized Gate Threshold Voltage vs Temperature**




**Figure 14. Normalized On Resistance vs Temperature**




**Figure 15. Source-drain Diode Forward Characteristics**




**Figure 16. Unclamped Inductive Load Test Circuit**




**Figure 17. Unclamped Inductive Waveforms**




**Figure 18. Switching Times Test Circuits For Resistive Load**



**Figure 19. Gate Charge Test Circuit**



**Figure 20. Test Circuit For Inductive Load Switching And Diode Recovery Times**




PACKAGE MECHANICAL

Table 12. TO-220 Mechanical Data

Symbol	millimeters			inches		
	Min	Typ	Max	Min	Typ	Max
A	4.40		4.60	0.173		0.181
b	0.61		0.88	0.024		0.034
b1	1.15		1.70	0.045		0.066
c	0.49		0.70	0.019		0.027
D	15.25		15.75	0.60		0.620
E	10		10.40	0.393		0.409
e	2.40		2.70	0.094		0.106
e1	4.95		5.15	0.194		0.202
F	1.23		1.32	0.048		0.052
H1	6.20		6.60	0.244		0.256
J1	2.40		2.72	0.094		0.107
L	13		14	0.511		0.551
L1	3.50		3.93	0.137		0.154
L20		16.40			0.645	
L30		28.90			1.137	
ØP	3.75		3.85	0.147		0.151
Q	2.65		2.95	0.104		0.116

Figure 21. TO-220 Package Dimensions




Note: Drawing is not to scale.



Table 13. TO-220FP Mechanical Data

Symbol	millimeters			inches		
	Min	Typ	Max	Min	Typ	Max
A	4.40		4.60	0.173		0.181
B	2.50		2.70	0.098		0.106
C	1.00		1.30	0.039		0.051
D	2.50		2.75	0.098		0.108
E	0.40		0.70	0.016		0.027
F	0.75		1.00	0.030		0.039
F1	1.15		1.70	0.045		0.066
F2	1.15		1.70	0.045		0.066
G	4.95		5.20	0.195		0.204
G1	2.40		2.70	0.094		0.106
H	10.00		10.40	0.393		0.409
L2		16.00			0.630	
L3	28.60		30.60	1.126		1.204
L4	9.80		10.60	0.385		0.417
L5	3.30		3.50	0.129		0.137
L6	15.90		16.40	0.626		0.645
L7	9.00		9.30	0.354		0.366
P			1.60			0.063
V		5°			5°	
V1	50°		100°	50°		100°
V2	44°		46°	44°		46°
∅	3.00		3.20	0.118		0.126

Figure 22. TO-220FP Package Dimensions



Note: Drawing is not to scale.

**REVISION HISTORY**

**Table 14. Revision History**

<b>Date</b>	<b>Revision</b>	<b>Description of Changes</b>
January-1998	1	First Issue
14-Apr-2004	2	Stylesheet update. No content change.

Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is a registered trademark of STMicroelectronics.  
All other names are the property of their respective owners

© 2004 STMicroelectronics - All rights reserved

STMicroelectronics GROUP OF COMPANIES

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan -  
Malaysia - Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States

[www.st.com](http://www.st.com)